



FUSES, DV/Dt, THERMAL TRIPS OPTIONAL.  
 FOR B6H USE MCD/xx  
 FOR B6U USE MDD/xx

TOLERANCES UNLESS SPECIFIED  
 UNLIMITED DIMENSIONS TO BE ± 0.2  
 ANGLES ± 0° 30°  
 HOLES + 0.1 - 0.02

REMOVE SHARP EDGES  
 ALL DIMENSIONS IN MILLIMETRES  
 CHAMFER ALL THREADS AT 45 TO  
 ROOT DIAMETER.

POWERSEM LTD OWNS THE COPYRIGHT OF THIS DRAWING WHICH IS  
 SUPPLIED IN CONFIDENCE AND WHICH MUST NOT BE USED FOR ANY PURPOSE OTHER THAN  
 THAT FOR WHICH IT IS SUPPLIED, AND MUST NOT BE REPRODUCED WITHOUT PERMISSION  
 IN WRITING FROM THE OWNERS. © POWERSEM LTD.

TITLE: B6C MCC500/xx PS292/350BF

JOB:

MAT'L:

SPEC.

FINISH:

SCALE 1:3

DRAWN PB

CHK'D MP

MOD. No

ISSUE No

1/01.06.04

DRG.No.B 020961

ASSEMBLY DN:  
 ASSEMBLY ON

THIRD ANGLE PROJECTION

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100



