



When Hi/Lo trips fitted
Mount left & right respectively

FUSES, Dv/Dt, THERMAL TRIPS OPTIONAL.

FOR B6H USE MCD/xx

FOR B6U USE MDD/xx

TOLERANCES UNLESS SPECIFIED UNLIMITED DIMENSIONS TO BE ± 0.2 ANGLES ± 0° - 30° HOLES + 0.1 - 0.02	REMOVE SHARP EDGES ALL DIMENSIONS IN MILLIMETRES CHAMFER ALL THREADS AT 45 TO ROOT DIAMETER.	POWERSEM LTD OWNS THE COPYRIGHT OF THIS DRAWING WHICH IS SUPPLIED IN CONFIDENCE AND WHICH MUST NOT BE USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS SUPPLIED, AND MUST NOT BE REPRODUCED WITHOUT PERMISSION IN WRITING FROM THE OWNERS. © POWERSEM LTD.	TITLE: B6C MCC310/xx PS385/400B				JOB:		
			MATERIAL:		FINISH:		SCALE 1:3		SPEC.
ASSEMBLY DN:		THIRD ANGLE PROJECTION		MOD. No		DRAWN PB		CHK'D MP	
ASSEMBLY DN:				ISSUE No 1/01.06.04				DRG.No.B 020980	