



FUSES, Dv/Dt, THERMAL TIPS OPTIONAL.
 FOR B2U/H/C OMIT CTR PHASE
 FOR B6U USE MDD/xx
 FOR B6H USE MCD/xx

TOLERANCES UNLESS SPECIFIED
 UNLIMITED DIMENSIONS TO BE ± 0.2
 ANGLES ± 0° 30'
 HOLES + 0.1 - 0.02

REMOVE SHARP EDGES
 ALL DIMENSIONS IN MILLIMETRES
 CHAMFER ALL THREADS AT 45 TO
 ROOT DIAMETER.

POWERSEM LTD OWNS THE COPYRIGHT OF THIS DRAWING WHICH IS
 SUPPLIED IN CONFIDENCE AND WHICH MUST NOT BE USED FOR ANY PURPOSE OTHER THAN
 THAT FOR WHICH IT IS SUPPLIED, AND MUST NOT BE REPRODUCED WITHOUT PERMISSION
 IN WRITING FROM THE OWNERS. © POWERSEM LTD.

TITLE: B6C MCC310/xx PS385/400BF

JOB:

MAT'L:

SPEC:

FINISH:

SCALE 1:3

DRAWN PB

CHK'D MP

MDD No

ISSUE No

1/21.11.05

DRG.No.B 020984

ASSEMBLY DN:
 ASSEMBLY DN

THIRD ANGLE PROJECTION