



DRG.No.B 020985B2

POWERSEM LTD.



When HI/Lo trips fitted
Mount left & right respectively

FIXINGS M6 CLEAR

FOR B2C USE MCC
FOR B2HZ USE MCC+MDD
FOR B2HK USE MCD
FOR B2U USE MDD

TOLERANCES UNLESS SPECIFIED
UNLIMITED DIMENSIONS TO BE ± 0.2
ANGLES $\pm 0^\circ 30'$
HOLES $+ 0.1 - 0.02$

REMOVE SHARP EDGES
ALL DIMENSIONS IN MILLIMETRES
CHAMFER ALL THREADS AT 45 TO
ROOT DIAMETER.

POWERSEM LTD OWNS THE COPYRIGHT OF THIS DRAWING WHICH IS
SUPPLIED IN CONFIDENCE AND WHICH MUST NOT BE USED FOR ANY PURPOSE OTHER THAN
THAT FOR WHICH IT IS SUPPLIED, AND MUST NOT BE REPRODUCED WITHOUT PERMISSION
IN WRITING FROM THE OWNERS. © POWERSEM LTD.

TITLE: B2C MCC500/xx PS385/400BF

JOB:

MAT'L:

SPEC.

FINISH:

SCALE 1:3

DRAWN PB

CHK'D MP

MDD No

ISSUE No

1/21.11.05

DRG.No.B 020985B2

ASSEMBLY DN:
ASSEMBLY DN

THIRD ANGLE PROJECTION